

Diesel powered machines for animal feed pellets production
Unité de fabrication de granulés de 2,5 à 10mm
Model SL-200A, SL-230A

Product HS code for import custom use: 84361000

Feed particle machine also known as pellet feed molding machine, it is a special feed processing machine mainly for manufacturing pellet feed by crushed powder of corn, soybean meal, straw, grass and rice husk etc., with or without liquid added in the processing procedure, the pellet feed could be produced in control humidity to serve different needs of users.

SL-200A, 230A pellet feed machine is a kind of flat mold pellet machine good for small to medium size of Aquaculture farms, Poultry farm and Livestock farms, also good as well to be used in food processing industries.



Model No.	SL-200A	SL-230A
Diesel engine Power	15hp	22hp
Flat mould diameter	200mm	230mm
Pelleted Size (dia.)	2.5~10mm	2.5~10mm
Water content	12~20%	12~20%
Feed granulating producing capacity	200~300kgs/hour	300~400kgs/hour
Unit weight	230kgs	260kgs
Package dimension	1180*560*950mm	1180*560*950mm

Features:

1. In Simple and compact structure with low noise running.
2. Powder feed or grass fodder could be granulated with or without liquid. A little liquid adding is to adjust the hardness of the pellet feed, without liquid it is even better as it remains the original moisture of raw materials to enable the pellet feed a longtime feed storage efficiently.
3. Produced by dry powder materials, the pellet feed could be in good hardness, smooth surface and an average pellet form, this could improve the digestion and absorption of nutrients during the animal

feeding.

4. In the pellet forming process, under a big pressure the pancreatic resist factors of powder feed e.g. Cereals and legumes will get molecular structure variation, which helps a reduction of adverse effects in animals digestion. At the same time, the varied pancreaticozym can kill a variety of parasite eggs and other pathogenic microorganisms, thus the different kinds of parasites and digestive diseases could be highly reduced

	Name	Granulating mould
	Material	Carbon steel
	Pelleted size (Dia.)	2.5/3/4/6/8/10mm
	Mould charge (for extra needs)	Consult us
	Unless specified, the machine will be supplied in 4mm pellet mould.	

Optional Screw Lifter

- * Working capacity matching the Feed particle machine.
- * Length 2m, Lifting tube dia.160mm.
- * With electric motor 2.2KW.
- * The below picture is to show you how the screw lifter works with the feed particle machine.

